

SECTION 907 CONCRETE CURBS, WALKS, DRIVES AND INCIDENTAL PAVING

907-3 CONSTRUCTION: At the end of this subsection add the following:

(h) Driveway Crossing for Sanitary Sewer Construction: A driveway crossing is associated with sanitary sewer gravity line and force main installations under an existing driveway regardless of driveway material. Contractor may choose to install pipe across driveway by approved trenchless or open cut methods. If the pipe installation requires a portion of the driveway to be temporarily removed and replaced it shall be done in accordance with the Contract Documents. Contractor shall maintain access to the property with stone, crushed concrete or gravel and shall be satisfactory to the Engineer, until the drive is replaced.

907-4 MEASUREMENT: At the end of this subsection add the following:

Measurement for driveway crossings for sanitary sewer construction shall be made on a linear foot basis in accordance with the pay limits designated in the Contract Documents.

907-5 PAYMENT: At the end of this subsection add the following:

Payment for driveway crossings for sanitary sewer construction shall be full compensation for all labor, materials and equipment to install pipe across driveway (regardless of construction method chosen by the Contractor). Depending of construction method proposed, Contractor shall include all costs associated with chosen construction method for pipe installation across driveway including sawcutting, removal, disposal, temporary access, and replacement of existing drive (in kind) if necessary in accordance with the Contract Documents.

907-6 PAY ITEMS: At the end of this subsection add the following:

9079000	Driveway Crossing for Sanitary Sewer Construction	Linear Foot
---------	---	-------------

****Designer Note****

This item is only used for special cases. In particular, when installing long runs of force main with many driveway crossings. This item allows contractor to choose installation method across driveways (bore or open cut).